

ROBIN /HOPPT PLATE COMPACTOR SPECIFICATION

<p>MODEL</p>	
EY-203D	
<p>ENGINES</p>	
Type	Air-cooled, 4-cycle single cylinder, side valve, gasoline engine
Displacement	183 mL(cc)
Maximum output	3.7/4000 (5.0/4000) kW/rpm (HP/rpm)
Direction of Rotation	Counterclockwise, as viewed from P.T.O. Shaft side
Lubricant	Automotive detergent oil (AP1/SE or higher grade, SAE/10W-30etc.)
Oil capacity	0.6 Liter
Fuel	Automotive Gasoline (Unleaded)
Fuel Tank Capacity	3.8 Liter
Spark plug	NGK B-6HS or BR-6HS, (CHAMPION L86C or RL86C)
Starting system	Recoil starter
Dry weight	15 Kg
Dimensions (LxWxH)mm	303x318x392
<p>PLATE</p>	
MODEL	CPT 90B
Dimension(L*W*H)-mm(in)	980*490*850(38.6*19.3*33.5)
Operating weight-kg(lb)	98(198)
Plate size (L*W)-mm (in)	90*490(19.3*19.3)
Working speed-km/h (mph)	12-1.3(0.75-0.81)
Vibration frequency-Hz (V.P.M)	100(6000)
Centrifugal force-kg(lb)	1630(3594)
Compacted area-m2/h(ft2/h)	530-590(5705-6351)
Compaction depth (depending on soul) -cm(in)	30(11.8)